

## Claims

1. An electric pipette (1) comprising a body (2), a tip part (4), a hook part (5), a push-button part (6) and a display part (7), said body (1) having a vertical axis (3),  
5 **characterised** in that at least one of the parts selected from the group consisting of the hook part (5), the push-button part (6) and the display part (7) is rotatable about the vertical axis (3) of the electric pipette (1).
2. An electric pipette (1) according to claim 1, **characterised** in that at least one of  
10 the parts (5, 6, 7) is rotatable over 0-360 °.
3. An electric pipette (1) according to claim 1, **characterised** in that at least one of the angles  $\varphi_1$ ,  $\varphi_2$  or  $\varphi_3$  is in the range  $-90 - 90^\circ$ .
- 15 4. An electric pipette (1) according to claim 1, **characterised** in that at least one of the angles  $\varphi_1$ ,  $\varphi_2$  or  $\varphi_3$  is in the range  $-70 - 70^\circ$ .
5. An electric pipette (1) according to claim 1, **characterised** in that at least one of the angles  $\varphi_1$ ,  $\varphi_2$  or  $\varphi_3$  is in the range  $-50 - 50^\circ$ .  
20
6. An electric pipette (1) according to any of claims 2-5, **characterised** in that the axis of rotation (8) of the display part (7) additionally is at an angle  $\alpha$  in the range 0-60 ° to the vertical axis (3) of the electric pipette (1).
- 25 7. An electric pipette (1) according to any of claims 2-5, **characterised** in that the axis of rotation (8) of the display part (7) additionally is at an angle  $\alpha$  in the range 0-50 ° to the vertical axis (3) of the electric pipette (1).
8. An electric pipette (1) according to any of claims 2-5, **characterised** in that the  
30 axis of rotation (8) of the display part (7) additionally is at an angle  $\alpha$  in the range 0-40 ° to the vertical axis (3) of the electric pipette (1).